

PROTECTIVE MATERIALS



Flat cap

No.: FHWZ-01

Scope of use

Cap requirements appearance should be clean, beautiful, cap requirements appearance should be free of burrs, cap requirements appearance should be free of stains, cap requirements appearance should be uniform color distribution, cap not less than 17g/m nonwoven fabric.

Technical parameters

1. Material properties: PP30G; sterilization
2. Model: round cap
3. Specification: 20 type
4. Executive standard: YY/T1642-2019
5. Carton size: 63*45*60cm; 5000 tops/carton
6. Box weight: 23KG



Spring-loaded cap

No.: FHWZ-02

Product Parameter.

Cap requirements appearance should be clean, beautiful, cap requirements appearance should be free of burrs, cap requirements appearance should be free of stains, cap requirements appearance should be uniform color distribution, cap not less than 17g/m2 nonwoven fabric.

Technical parameters

1. Material properties: PP20G; sterilization
2. Model: strip cap
3. Specification: 20 type
4. Executive standard: YY/T1642-2019
5. Carton size: 63*45*60cm; 5000 caps/carton
6. Box weight: 22KG



Spring-loaded cap

No.: FHWZ-03

Product Parameter.

Cap requirements appearance should be clean, beautiful, cap requirements appearance should be free of burrs, cap requirements appearance should be free of stains, cap requirements appearance should be uniform color distribution, cap not less than 17g/m nonwoven fabric.

Technical parameters

1. Material properties: SMS
2. Model: round cap
3. Specification: 20 type
4. Execution standard: YY/T0506.2-2016
5. Outer box size: 400 caps/box
6. Shelf life: 5 years



VisiOTG-A Asian Visitor Glasses

No.: FHWZ-04

Technical parameters

1. Designed for Asian face, anti-impact, anti-scratch and anti-fog.
2. Can be worn outside the corrective glasses can also be used as visiting glasses
3. Non-anti-fog models, anti-fog models



Pk Impact Glasses

No.: FHWZ-05

Technical parameters

1. Polycarbonate lenses, anti-impact, side ventilation, wide field of vision can be worn with myopia correction glasses, can also be used as a guest glasses.



Medical Isolation Eye Mask

No.: FHWZ-06

Technical parameters

1. Complex People's Republic of China national "GB14866-2006 personal eye protection technical requirements"
2. The medical isolation eye mask has an adjustable belt, soft materials, durable

PROTECTIVE MATERIALS



Disposable Activated Carbon Mask

No.: FHWZ-07

Scope of use

Hardware, chemical, paint, spray paint, power plant, agricultural about, electroplating plant and other industries.

Technical Parameters

1. Metal bar (nose clip), rubber band webbing on both sides. High-efficiency activated carbon cloth layer, filtration odor (concentration is very small), after electrostatic treatment of the filter layer, effective barrier filter and adsorption of very fine harmful industrial dust, to prevent silicosis
2. Washing-free, maintenance-free, convenient and practical
- 3 to meet national standards 4.50pcs/box, individually packaged



Disposable industrial dust mask

No.: FHWZ-08

Product Parameter.

Disposable for cleanroom use, medical, workshop, etc.

Technical Parameters

- 1.90% filtration for 0.1 micron particles. Efficiency
- 2.Meet the national standard
- 3Color: blue/white/green



CRPI Protective Mask (3-D)

No.: FHWZ-09

Scope of use:

Suitable for protection against non-oil particles in the air.

Technical Parameters

1. Packing: 200pcs/ctn.
- 2.Packing size:14x20cm
- 3.Carton size:43x32x30cm
- 4.Execution standard:GB2626-2006/GB/T32610-2016



CRPI Protective Mask (Flat)

No.: FHWZ-10

Scope of use

Suitable for protection against non-oily particles in the air.

Technical Parameters

1. Packing: 200pcs/ctn.
- 2.Packing size:14x20cm
- 3 Carton size: 43x32x30cm
- 4.Execution standard:GB2626-2006/GB/T32610-2016



Rubber Medical Gloves

No.: FHWZ-11

Usage:

Widely used in food processing, pharmaceuticals, packaging industry and medical and health care industry etc.

Technical Parameters

1. Curved linen with powder is a disposable hygiene product.
2. Specification: 6, 7, 7, 8, 8?



White Beaded Dot Gloves

No.: FHWZ-12

Technical Parameters

1. PVC dot beads on the palm, with good anti-slip function
2. Cotton/nylon

PROTECTIVE MATERIALS



White Beaded Dot Gloves

No.: FHWZ-12

Technical Parameters

1. PVC dot beads on the palm, with good anti-slip function
2. Cotton/nylon



Disposable latex examination gloves

No.: FHWZ-13

Technical Parameters

1. Standard: ASTM D3578/EN455
2. Material: natural high quality latex
3. Shelf life: 5 years.
4. Storage: Store in a place protected from light and humidity.
5. Features
 1. Protection against harmful substances
 2. Beaded cuffs are easy to put on and help prevent rollbacks
 3. Use USP grade absorbable corn starch
 6. Available in pink, white



Nitrile Examination Gloves

No.: FHWZ-14

Technical Parameters

1. Standard: ASTM D6319
2. Material: synthetic nitrile rubber
3. Shelf life: 5 years
4. Storage: Store in a place protected from light and moisture.
5. Features
 1. Excellent strength and better puncture resistance
 2. Beaded cuffs are easy to put on and help prevent rollbacks
 3. Super thin and high strength texture improves tactile feel
 6. Powder free non-sterile



CRPI Protective Mask (Flat)

No.: FHWZ-15

Technical Parameter

1. sponge size: 240*30*20mm
2. Specification (LxW): ≥33x22cm
3. Made of polymer material shield, foam strips and fixed devices.
4. head circumference size adjustable

number	Material Properties	Style	Sponge elastic band	Model No.	Standard	Outer box size	Weight
1	PET	Sponge elastic band	Protective	S-01	GB14866-2006	68*37*31CM;200pcs/box	8.5KG
2	PVC+PC	Four-hole valve	Protective	P-01	GB14866-2006	51.5*42.5*48.5CM;200pcs/box	7KG
3	PET	PET	Protective type	S-01	GB14866-2006	50*34*38CM;350pcs/box	9.24KG

PROTECTIVE MATERIALS



Medical isolation shoe covers

No.: FHWZ-16

Technical Parameter

1. Water permeability must be $\geq 1.67\text{kPa}$.
2. This product is made of PE material, subject to sample measurement.
3. Surface moisture resistance ≥ 2 levels
4. Product breaking strength (N) 240 vertical and 40 horizontal
5. Elongation at break (%) 215 vertical and 15 horizontal
6. Product resistance to synthetic blood penetration grade ≥ 2 in line with GB19082-2009 test

number	Material properties	Style	Model	Specification	Execution standard	Outer box size	Weight
1	39*50CM; PE shoe cover;16 silk	Tall 16 silk PE shoe cover	Tall Shoe Cover	M size	YY/T 1633-2019	52*33*28CM;250pairs/box	9.5KG
2	65G PP+PE Laminating Strip; 37*48CM	Tall Shoe Cover with Double Ribs	Tall Shoe Cover	Size M	YY/T 1633-2019	50*38*40CM;100pairs/box	7KG
3	65G PP+PE Film Lamination Strip;37*40CM	Midsole with single stripe	Medium Shoe Covers	Size M	YY/T 1633-2019	50*38*40CM;100pairs/box	6.5KG
4	65G PP+PE Film Non-Press Strip;37*48CM	Tall shoe cover with double rib	Tall Shoe Cover	Size M	YY/T 1633-2019	50*38*40CM;100pairs/box	6.5KG
5	65G PP+PE Film Lamination Strip;37*47CM	Tall compression band single band	Tall Shoe Covers	M size	YY/T 1633-2019	50*38*40CM;100pairs/ctn	7KG
6	65G PP+PE Film Lamination Strip;25*30CM	Medium Compression Strip Single Rib	Mid Calf Shoe Covers	Size S	YY/T 1633-2019	50*38*40CM;100pairs/ctn	6KG
7	65G PP+PE laminating non-cripp strip;37*48CM	Tall non-stripe non-slip sole	Tall Shoe Covers	Size M	YY/T 1633-2019	50*38*40CM;100pairs/box	7.5KG
8	65G PP+PE laminating strip 37*48CM	Tall non-slip compression sole	Tall Shoe Covers	Size M	YY/T 1633-2019	50*38*40CM;100pairs/box	8KG

PROTECTIVE MATERIALS

Medical isolation shoe cover (non-woven shoe cover)



No.: FHWZ-17

Technical Parameter

1. Made of non-woven fabric, subject to sample measurement.
2. Consistent color and luster, clean surface, no damage, stains, mildew and odor.
3. The nonwoven fabric used for shoe covers supplied in non-woven form shall not be less than 15g/square.

Material Properties	Style	Model	Specification	Standard	Outer box size	Box weight
PP 25G; 40*16CM	Nonwoven Shoe Cover	low-cut shoehorn	M	YY/T 1633-2019	63*45*60.50pairs/bag. 2500pairs/ctn	20.5KG



Disposable Dustproof Clothing

No.: FHWZ-18

Scope of use

Suitable for use in dusty working environments.

Technical Parameter

Non-woven material

Characteristics: excellent anti-tear performance, durable; front zipper, elastic cuffs; with a cap, the brim and trouser legs are tied with an elastic band to strengthen the protective properties

Medical Disposable Protective Gown

No.: FHWZ-19

Technical Parameter

1. The hydrostatic pressure of the key part of the protective clothing should be not less than 1.67Kpa(17cm H2O).
2. The moisture permeability of protective clothing material should be not less than 2500g/(m2.d).
3. Protective clothing anti-synthetic blood penetration should not be less than 2 levels (1.75kpa)
4. The water staining level of the outer side of the protective clothing should be not less than 3 levels.
5. The breaking strength of the key parts of the protective clothing materials should not be less than 45N.
6. Protective clothing key parts of the material and the seams of non-oil particles should be not less than 70% filtration efficiency
7. The charged amount of protective clothing should be no more than 0.6uC/piece.
8. The total number of bacterial colonies $\leq 200\text{CFU/g}$, the total number of fungal colonies $\leq 100\text{CFU/g}$



Material Properties	Style	Model	Specification	Standard	Outer box size	Box weight
PP+PE Laminating Strip 65G	Non-legged	Aseptic One-piece	160/165/175/180/185	GB19082-2009	63*53*40CM,50pcs/ctn	15KG
PP+PE laminating strip 65G	Non-legged	Aseptic type (with foot cover)	160/165/175/180/185	GB19082-2009	63*53*48CM,50pcs/ctn	18KG

PROTECTIVE MATERIALS



Medical disposable isolation gowns

No.: FHWZ-20

Technical Parameter

1. Moisture resistance: >3 levels, surface moisture permeability (g / (m-d)) 2500, water permeability (kPa) = 1.67
2. breaking strength (N) longitudinal $\geq$ 45 horizontal 45, elongation at break (%) longitudinal $\geq$ 15 horizontal $\geq$ 15
3. Resistance to synthetic blood penetration>2 grade

Material Properties	Style	Model	Specification	Standard	Outer box size	Box weight
63GPP+PE laminated non-strips	Non-compression	One-piece	175L/180XL/185XXL	GB19082-2009	50*30*60CM,50pcs/box	10KG
63GPP+PE laminated non-striped	Non-Pressing	One-piece	175L/180XL/185XXL	GB19082-2009	63*53*48CM,50pcs/box	11.5KG



Liquid hand soap

Ref: FHWZ-21

Technical Parameter

1. Unique moisturizing and refreshing formula, thoroughly clean and disinfect the skin.
2. A variety of brands, a variety of packaging specifications and sizes to choose from
3. Item No.:GA12-1900

Material Properties	Style	Model	Specification	Standard	Outer box size	Box weight
PP+PE lamination 45G	Reverse	Hanging Gown	175L	YY/T0506.2-2016	50*30*60CM,100pcs box	9.8KG
PP 25G	Reverse	Hanging Gown	175L	YY/T0506.2-2016	50*30*60CM,150pcs/box	9.5KG
SMS 45G	Reverse	Hanging Gown	175L	YY/T0506.2-2016	50*30*60CM,80pcs/box	12.5KG



Air sterilizer

No.: FHWZ-22

Technical Parameter

1. Power: 100W
2. Product size: 350*230*670mm
3. Voltage and frequency: 220V/50Hz optional 110V/60Hz
4. Wind speed adjustment: 1 gear-2 gear-3 gears
5. Applicable area: 30-50m²
6. Net weight: 4.4kg
7. Sterilization mode: UV irradiation + ozone + activated carbon + primary filtration (four-in-one disinfection and purification)

PROTECTIVE MATERIALS



Air sterilizer

No.: FHWZ-23

Technical Parameter

1. Power: 100W
2. Product size: 350*230*670mm
3. Voltage and frequency: 220V/50Hz optional 110V/60Hz
4. Wind speed adjustment: 1 gear-2 gear-3 gears
5. Applicable area: 30-50m²
6. Net weight: 4.4kg
7. Sterilization mode: UV irradiation + ozone + activated carbon + primary filtration (four-in-one disinfection and purification)



Wall-mounted Air Sterilizer

No.: FHWZ-24

Technical Parameter

1. Power: 95W
2. Product size: 275*845*160mm
3. Voltage and frequency: 220V/50Hz optional 110V/60Hz
4. Wind speed adjustment: 1 gear-2 gear-3 gears
5. Applicable area: 20-30m²
6. Net weight: 1.5kg
7. Sterilization mode: UV irradiation + ozone + primary filtration + negative ions (four-in-one elimination of Purification)



Foldable Multi-Purpose Sterilization Kit

No.: FHWZ-25

Technical Parameter

1. Power: 3W
2. Product size: 280 * 190 * 135mm
3. Product material: polyester material
4. Rated voltage: DC5V
5. Product features: foldable, easy to carry, does not take up space
6. Lamp life: 10000H
7. Control mode: push button switch
8. Product net weight: 0.4kg
9. UV wavelength: 253.7nm+185nm



Multi-functional large-capacity sterilization kit

No.: FHWZ-26

Technical Parameter

1. Product power 3W
2. Product size: 400*300*300mm
3. Product material: Oxford cloth fabrics
4. Rated voltage: DC5V
5. Product features: low energy consumption, low temperature, Long life, large capacity
6. Lamp life: 10000H
7. Control mode: magnet switch
8. Product net weight: 1.15kg
9. UV wavelength: 253.7nm+185nm



Car Sterilizer Lamp (Built-in Blower)

No.: FHWZ-27

Technical Parameter

1. Power: 3.5W
2. Product size: 6363*175mm
3. Input voltage: USB plug and play, Charger, adapter
4. Fan speed: 6500rpm
5. Applicable area: 3-5m²
6. Purification speed: 60m³/h
7. Control mode: key switch
8. Net weight: 0.3Kg
9. Sterilization mode: ultraviolet irradiation + negative ion purification + ozone sterilization



Portable Handheld Sterilizer Wand

No.: FHWZ-28

Technical Parameter

1. Power: 3.5W
2. Size: 265*41*38mm
3. Product material: ABS material
4. Killing characteristics: mobile disinfection
5. Battery supply: Alkaline 5 batteries (4XAA)
6. Lamp life: 30000H
7. Control mode: key switch
8. Net weight: 0.2Kg
9. UV wavelength: 253.7nm

PROTECTIVE MATERIALS



Portable Cell Phone Sterilization Box

No.: FHWZ-29

Technical Parameter

1. Product power: 2W/2 Product size: 227*125*50mm
2. Product material: ABS material
3. Kill features: mobile disinfection
4. Input voltage: USB plug and play, Charging treasure, adapter
5. Lamp life: 30000H
6. Control mode: key switch
7. Product net weight: 0.2Kg
8. UV wavelength: 253.7nm



UV Sterilization Stand Lamp

No.: FHWZ-30

Technical Parameter

Lamp Power	Lamp Length	Recommended use range	Length of bracket	UV intensity	Standard life
6W	212mm	Sterilization Cabinet	232mm	18uw/cm ²	8000H
8W	288mm	Shoe Cabinet	314mm	28uw/cm ²	8000H
10W	311mm	Bathroom	350mm	30uw/cm ²	8000H
20W	589mm	20 sq. ft.	615mm	75uw/cm ²	8000H
30W	894mm	30 square feet	915mm	107uw/cm ²	8000H
40W	1199mm	40 square feet	1220mm	117uw/cm ²	8000H



Integrated ultraviolet sterilization lamp

No.: FHWZ-31

Technical Parameter

1. Power: 36W/80W
2. Product Size: 200*54mm(15W)/230*54mm(25W)/270*62mm(36W)/400*85mm(80W)
3. Lamp interface: E27
4. Rated voltage: 220V/50Hz optional 110V/60Hz
5. Lamp life: 8000H
6. Control mode key switch
7. Applicable area: 15m²(15W)/<25m²(25W) <36m²(36W)/<80m²(80W)
8. UV wavelength: 253.7nm/2537nm+185nm LYL-YTH-03



Folding - UV Sterilization Table Lamps

No.: FHWZ-32

Technical Parameter

1. Power: 38W
2. Size: 170*170*420mm
3. Product material: ABS material
4. Rated voltage: 220V/50Hz optional 110V/60Hz
5. Applicable area: <40m²
6. Lamp life: 8000H
7. Control mode intelligent remote control + three timing
8. Product net weight: 0.55Kg
9. UV wavelength: 253.7nm/253.7nm+185nm



Guardrails

No.: FHWZ-33
Scope of use

Suitable for outdoor leisure series products in airports, banks, star hotels lobby, guest rooms, Chinese and Western restaurants conference centers, parks, high-level residential communities, exhibition halls and so on.



Barrier pillar

No.: FHWZ-34
Technical Parameter

1. PE and other synthetic materials
2. Specification: Length 500*Upper width 160*Lower width 400 high 500MM neutral
3. Weight 4.3KG



Reflective tripods,
road god lights

No.: FHWZ-35
Scope of use

Suitable for road construction airports, hotels and other places, for night lighting to improve the role of warning.
Reflective Tripod / Road God Lamp



Yeller

No.: FHWZ-36



Visit Factory

360° VR panoramas we provide

<http://www.yrftextile.com>

Email: info@yrftextile.com

Whatsapp: +8613702995607